

Exinda Network Orchestrator 4062 is our most powerful branch office appliance designed for customers with rapidly growing bandwidth needs and require the flexibility to upgrade in the future. The 4062 can be deployed as a 100 Mbps system and easily upgraded to 1 Gbps, with expandable network interfaces and remote management capabilities. If you're concerned about scaling to meet the future needs of your network, the 4062 is for you.

Traffic Shaping

Shaping Throughput	1 Gbps
Concurrent Flows	220,000
New Connections Rate	10,000/s
Packets Per Second	200,000/s
Traffic Policies	1024

Traffic Acceleration

Acceleration Throughput	30 Mbps
Edge Cache Throughput	50 Mbps
Optimized Connections	6,000

Network Diagnostics

APS Objects	250
SLA Objects	250
PDF Reports	60

Interface Capabilities

Built in NICs	3 x 1G bypass bridge pair
Additional NIC Slots	1 full height expansion slot
Available NICs	Copper: 5 x 1G bypass bridge pair Fiber: 2 x 1G bypass bridge pair
Management Ports	RJ-45 serial console and dedicated
IPMI	Shared with dedicated management interface

Physical Characteristics

Form Factor	1U rackmount
Dimensions (HxWxD)	44 mm x 436 mm x 300 mm (1.72" x 16.81" x 11.81")
Power	Internal – autoranging
Power Rating	17W @ 0.13A (Idle), 22W @ 0.16A (Max)
Weight	5.0 kg (11 lbs)
Data Store / Cache Size	864 GB
Environment	Continuous operation: 0°C to 40°C (32°F to 104°F), 5%-90% operating humidity

