

The Exinda Appliance 12064 is Exinda's large range data center grade appliance. Architected to serve the large data centers and service provider networks, the 12064 is built to scale with your business. With exceptional power and bandwidth capacity, our most powerful appliance can protect application SLAs no matter what the network throws at it. Built for companies and service providers with extremely high traffic volume and whose business depends on meeting and exceeding network application SLAs.

<b>Traffic Shaping</b>	
Shaping Throughput	20 Gbps*
Concurrent Flow	1,800,000
New Connection Rate	38,000/s
Packets Per Second	1,800,000/s
Traffic Policies	5100
<b>Traffic Acceleration</b>	
Acceleration Throughput	2 Gbps
Edge Cache Throughput	500 Mbps
Optimized Connections	49,000
<b>Network Diagnostics</b>	
APS Objects	400
SLA Objects	400
PDF Reports	150
<b>Hardware Specifications</b>	
Form Factor	Desktop or 2U rack mount
Dimensions (HxWxD)	86.8 mm x 482 mm x 715 mm (3.41" x 18.97" x 28.17")
Power	Dual hot-plug redundant power - 750 W
Power Rating	100–240 V AC, 50/60 Hz autoranging, 5 A - 10.5 A
Weight*	18.6 kg (41.0 lb)
RAM / MEM	256 GB RDIMM, 3200 MT/s, Dual Rank
Data Store / Cache Size	SSD 1.6 TB, RAID 1
Environment	10°C to 35°C (50°F to 95°F), 10% to 80% relative humidity
<b>Interface Capabilities</b>	
Built in NICs	None
Additional NIC Slots	7 full height
Management Ports	DB-9 serial console and dedicated RJ-45 management interface
IPMI	Dedicated RJ-45 interface

\* The weight may be higher in case of different hardware configuration.












Talk to an Exinda appliance expert today

[sales@gfi.com](mailto:sales@gfi.com)

[www.gfi.com/exinda](http://www.gfi.com/exinda)

## Available NICs

	EXN-RJ45-2P-FH 2-port 1 Gbps	EXN-RJ45-4P-HF 4-port 1 Gbps	EXN-RJ45-6P-F 6-port 1 Gbps	EXN-RJ45-2P-10G 2-port 10 Gbps
				
<b>Connector type</b>	<b>RJ-45</b>	<b>RJ-45</b>	<b>RJ-45</b>	<b>RJ-45</b>
<b>slot 1</b>	Yes	Yes	Yes	Yes
<b>slot 2</b>	Yes	Yes	Yes	Yes
<b>slot 3</b>	Yes	Yes	Yes	Yes
<b>slot 4</b>	Yes	Yes	Yes	Yes
<b>slot 5</b>	Yes	Yes	Yes	Yes
<b>slot 6 (Half)</b>	Slot not usable			
<b>slot 7</b>	Yes	Yes	Yes	Yes
<b>slot 8</b>	Yes	Yes	Yes	Yes

	EXN-FIB-2P-MS-FH 2-port 1 Gbps Short Range	EXN-FIB-2P-SL-FH 2-port 1 Gbps Long Range	EXN-FIB-4P-MS-F 4-port 1 Gbps Short Range	EXN-FIB-4P-SL-FI 4-port 1 Gbps Long Range	EXN-FIB10-2P-MS 2-port 10 Gbps Short Range	EXN-FIB10-2P-SL 2-port 10 Gbps Long Range	EXN-FIB40-2P-FH 2-port 40 Gbps Short Range	EXN-FIB10-4P-MS-F 4-port 10 G Short Range
								
<b>Connector type</b>	<b>LC</b>	<b>LC</b>	<b>LC</b>	<b>LC</b>	<b>LC</b>	<b>LC</b>	<b>MTP</b>	<b>LC</b>
<b>slot 1</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>slot 2</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>slot 3</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>slot 4</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>slot 5</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>slot 6 (Half)</b>	Slot not usable							
<b>slot 7</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>slot 8</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

\* The card fits in the half height slot when using the included half height bracket.

N/A - Not available in this slot for this hardware.



Talk to an Exinda appliance expert today

[sales@gfi.com](mailto:sales@gfi.com)

[www.gfi.com/exinda](http://www.gfi.com/exinda)